


Tier1

BloombergNEF



Lloyd's Syndicate 1910



ISO14001

ISO9001

ISO45001




M6 HIEFF TWIN MONO

SPDGxxx-156M


- Double glass (xxx=465~495W)
- Silver frame
- Black frame
- Full black

15 Yr quality guarantee | 30 Yr power warranty

■ SUNPRO Standard (Additional value from 30-year warranty)
 ■ Industry Standard



*SUNPRO Standard tiered warranty



WARRANTY & GUARANTEE

Linear output power guarantee
12 years: 91.9% power output
30 years: 82.1% power output



WITHSTAND STRONG

Snow load 5400Pa
Wind load 2400Pa



TWO-SIDED BENEFITS

High efficiency solar cells.
Effective working area of both sides >75%, with significant power increase. Capture more sunlight and turn it into electricity



R&D AND PRODUCTION

Advanced production line. The leading solar cell cutting process and multi busbar design with SUNPRO Technology.



HIGH EFFICIENCY

Efficiency can reach 21.06%. Excellent low light performance. Higher power output under the conditions of haze, overcast, etc.

Electrical parameters at standard test conditions (STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type	465W	475W	485W	495W
Max power(Pmax)	465	475	485	495
Max power voltage(Vmp)	43.94	44.34	44.74	45.14
Max power current(Imp)	10.58	10.71	10.84	10.97
Open circuit voltage(Voc)	52.89	53.29	53.69	54.09
Short circuit current(Isc)	11.17	11.35	11.53	11.71
Module Efficiency(%)	19.78	20.22	20.63	21.06
Max system voltage	DC 1500V(TUV)			
Maximum Series Fuse Rating	25A			


Electrical parameters at NMOT test conditions (Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s)

Typical type	465W	475W	485W	495W
Max power(Pmax)	347.5	354.9	362.3	369.7
Max power voltage(Vmp)	40.92	41.32	41.72	42.12
Max power current(Imp)	8.51	8.60	8.70	8.79
Open circuit voltage(Voc)	49.11	49.71	50.11	50.51
Short circuit current(Isc)	9.03	9.17	9.31	9.45

Electrical Characteristics with 15% Rear Side Power Gain (Take 485W as an example)

Back power gain	5%	15%	25%
Max power(Pmax)	509	534	558
Vmp/V(Total)	44.74	44.74	44.84
Imp/A(Total)	11.38	11.94	12.45
Voc/V(Total)	53.69	53.69	53.79
Isc/A(Total)	12.10	12.70	13.24

DIMENSIONS AND STRUCTURE



Mechanical Data


Dimensions	2094x1038x35mm
Weight	29.75kg
Glass	(F) 2.0mm coated high-transparent tempered glass (B) 2.0mm high-transparent glass
Output cables	4mm ² , symmetrical lengths 1100mm
Connectors	MC4 compatible IP68
Cell type	Mono-Crystalline PERC, 9BB, 166x83mm
Number of cells	156cells (Half-Cell)

Temperature Characteristics

Packing Configuration

Temp.Coeff.of Isc(TK Isc)	0.050%/°C	Container	40'HQ
Temp.Coeff.of Voc(TK Voc)	-0.284%/°C	Pieces per pallet	66
Temp.Coeff.of Pmax(TK Pmax)	-0.35%/°C	Pallets per container	11
Operating temperature	-40~+85°C	Pieces per container	726
Normal operating cell temperature	45±2°C		

I-V CHARACTERISTICS AT DIFFERENT IRRADIATION (Take 485W as an example)



Tests, Certifications and Warranties

Standard tests	IEC 61215, IEC 61730, IEC 61701, IEC 62716, PPP 58042
System certs	ISO 9001, ISO14001, ISO45001
Certifications	TUV, CE, WEEE, INMETRO FIRE CERTIFICATE C1
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Power tolerance	0~+3%
Junction box	IP 68
Warranties	15 years product warranty and 30 years 82.1% of power