



Description Interruttore automatico scatolato  
 Code MSXE 1000  
 No. of poles 4P  
 Rated current 1000 A  
 Release Electronic


#### ELECTRICAL CHARACTERISTICS

Standard	IEC/EN 60947-2	Execution	Fixed
Use category	A	DIN rail mounting	No
Rated frequency (Hz)	50 / 60	Can be equipped with motor operator	Yes
Rated operating voltage (Ue)	690 Vac	Compatible interlock	Lever – Cable
Rated impulse withstand voltage (Uimp)	8 kV	Terminals supplied	Front FB Extended
Overtoltage category	IV	Assembly position	Any
Insulation voltage (Ui)	800 V	Upline/downline power supply	Yes
Thermal regulation	0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In	Electrical life (415Vac)	4.000 cycles
Magnetic regulation	Electronic LSI	Mechanical life	10.000 cycles
Neutral protection	50% - 100% x Ir	Operating temperature	-5°C +65°C
Total power loss	248 W	Stocking temperature	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Weight (kg)	14.8
Rated short-time withstand current for 0,3s (Icw)	-	Width	280 mm
I <sub>dn</sub> regulation	-	Height	273 mm
DT regulation	-	Depth	103 mm

#### SERVICE BREAKING CAPACITY (ICU)

220/240Vac	85 kA	220/240Vac	85 kA
400/415Vac	50 kA	400/415Vac	50 kA
440Vac	50 kA	440Vac	50 kA
525Vac	30 kA	525Vac	30 kA
690Vac	20 kA	690Vac	20 kA
250Vdc	-	250Vdc	-

### DIMENSIONAL





Product Data Sheet

GWD9408

MSX

STANDARDS/APPROVALS

