



Description Rotary switch disconnector

Code MSS 250

No. of poles 3P

Rated current 250 A


ELECTRICAL CHARACTERISTICS

Standard	EN 60947-3
AC Rated operational voltage (Ue)	400V
DC Rated operational voltage (Ue)	220 V
AC Maximum operational voltage (Ue max)	690 V
DC Maximum operational voltage (Ue max)	500V
Rated insulation voltage (Ui)	800 V
Rated impulse withstand voltage (Uimp)	8 kV
Rated short-time withstand current for 1s (Icw)	9 kA
Rated short-circuit current making capacity (Icm)	30 kA
Conditional short-circuit current with fuse (Icc)	50 kA (gG 250A)
Power dissipation per pole	5,8 W
AC RATED OPERATIONAL CURRENT (Ie)	
AC-20A / AC-20B (690V AC)	250 A / 250 A
AC-21A / AC-21B (400V AC)	250 A / 250 A
AC-21A / AC-21B (500V AC)	250 A / 250 A
AC-21A / AC-21B (690V AC)	250 A / 250 A
AC-22A / AC-22B (400V AC)	250 A / 250 A
AC-22A / AC-22B (500V AC)	250 A / 250 A
AC-22A / AC-22B (690V AC)	125 A / 160 A
AC-23A / AC-23B (400V AC)	250 A / 250 A
AC-23A / AC-23B (500V AC)	250 A / 250 A
AC-23A / AC-23B (690V AC)	100 A / 125 A
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-

MECHANICAL CHARACTERISTICS

Mechanical life	10.000 cycles
Maximum number of auxiliary contacts that can be installed	1
Minimum cable size	95 mm ²
Maximum cable size (rigid/flexible)	150 / 70 mm ²
Maximum busbar width	32 mm
Rated tightening torque	20 Nm
Pre-arrangement for lock in OFF position	Yes (ø8 mm max)
Height	108 mm
Width (mm)	180
Depth	75 mm
Weight (kg)	1.6
DC RATED OPERATIONAL CURRENT (Ie)	
DC-20A / DC-20B (220V DC)	250 A / 250 A
DC-20A / DC-20B (400V DC)	250 A / 250 A
DC-20A / DC-20B (440V DC)	-
DC-20A / DC-20B (500V DC)	250 A / 250 A
DC-21A / DC-21B (220V DC)	250 A / 250 A
DC-21A / DC-21B (400V DC)	200 A / 200 A (2 poles in series for "+" and 1 pole for "-")
DC-21A / DC-21B (440V DC)	-
DC-21A / DC-21B (500V DC)	200 A / 200 A (2 poles in series for "+" and 1 pole for "-")
DC-22A / DC-22B (220V DC)	250 A / 250 A
DC-22A / DC-22B (400V DC)	200 A / 200 A (2 poles in series for "+" and 1 pole for "-")
DC-22A / DC-22B (440V DC)	-
DC-22A / DC-22B (500V DC)	-
DC-23A / DC-23B (220V DC)	200 A / 200 A
DC-23A / DC-23B (400V DC)	-
DC-23A / DC-23B (440V DC)	-
DC-23A / DC-23B (500V DC)	-

DIMENSIONAL





Product Data Sheet

GW97729

97 MSS Range

STANDARDS/APPROVALS

