


## Technical data

<b>QDX 630H</b>	
<b>Electrical characteristics</b>	<b>Mechanical characteristics</b>
Standards: EN 61439-1 and EN 61439-2, EN 62208	Degree of protection: IP 30 without door
Rated current (In): up to 250 A (wall-mounting), up to 630 A (floor-mounting)	IP 55 with glass/solid door
Rated operational voltage (Ue): up to 400 V ac	Impact resistance: IK 09 for glass door
Rated insulation voltage (Ui): up to 690 V ac	IK 10 for solid door
Rated impulse withstand voltage (Uimp): 6-8-12 kV 1.2/50 µs	Operating temperature: -5 °C ÷ 40 °C
Rated short-time withstand current for 1s (Icw): 20 kA (wall-mounting), 35 kA (floor-mounting)	Storage temperature: -25 °C ÷ 55 °C
Protection against indirect contacts: metal casing prearranged for earth connection	Sheet steel casing: 15/10 mm thick
	Galvanized metal sheet accessories: 15/10-20/10-25/10 mm thick
	Sheet metal painted with textured colour Grey RAL 7035 epoxy-polyester powder after phosphating

<b>FUNCTIONAL CHARACTERISTICS</b>	
Type of installation: indoors	Plinth (height 100 mm) palletizable by removing the front and rear panels
Capacity: 24/35 EN 50022 modules per row	Structures can be mounted side by side using the provided kit (only for floor-mounting boards)
Top and bottom cable entry through metal cable gland plates	Structure can be wall-mounted
Internal functional uprights with 25mm pitch drilled for the assembly of the equipment installation kits	Earthing by contact of metal parts
Segregation: form 1 and form 2a (floor-mounting)	Door assembly with reversible opening (right or left side)
	Board accessibility: front, side and rear


## Dimension tables

### STRUCTURE OF WALL-MOUNTING BOARD




### STRUCTURE OF FLOOR-MOUNTING BOARD

Size calculation of side by side n-structures (columns)  
 Width (mm) = (B1+B2+...+Bn)+50  
 Bn = nth column width (mm)  
 50 = size of 2 side panels




For technical information contact the Technical Assistance Service or visit [gewiss.com](http://gewiss.com)

## DOORS FOR WALL-MOUNTING BOARD




## DOOR FOR FLOOR-MOUNTING BOARD




For technical information contact the Technical Assistance Service or visit [gewiss.com](http://gewiss.com)

## WALL-MOUNTING BOARD INSTALLATION





## FLOOR-MOUNTING BOARD INSTALLATION





## WALL-MOUNTING BOARD STRUCTURE SECTION

WALL-MOUNTING BOARDS





## FLOOR-MOUNTING BOARD STRUCTURE SECTION

FLOOR-MOUNTING BOARDS





## WALL-MOUNTING BOARDS CABLE ENTRY (TOP/BOTTOM)



Single structure B=600



Single structure B=850





Structure with side by side compartment



## FLOOR-MOUNTING BOARDS CABLE ENTRY



Single structure

Bottom





External compartment



Bottom





Top



Top





Top





Structure with side by side compartment


Bottom




Top




## WINDOWED PANELS



## SOLID PANELS



## BACK-MOUNTING PANELS



Functional dimensions		Real dimensions	
B (mm)	H (mm)	B1 (mm)	H1 (mm)
600	200	442	198
600	400	442	398
600	600	442	598
600	800	442	798
600	1000	442	998
850	200	642	198
850	400	642	398
850	600	642	598
850	800	642	798
850	1000	642	998