

Keen 1500 USB

The power to control

PN: UPLI-LI150KU-CG01B
EAN: 6422956009571

Specifications

Capacity	1500 VA / 900 W
Type	Line-Interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	162 ~ 290 VAC
Frequency Range	50Hz / 60Hz (Auto Sensing)
Output	
Nominal Voltage	230 VAC
Accepted Voltage Range	207~253 VAC
Frequency Range (Batt. Mode)	50 Hz / 60Hz ± 1%
Power Factor	0.6 @ nominal voltage (100% load)
Waveform (Batt. Mode)	Simulated Sinewave
Transfer Time	Typical 4 ms
Overload Protection	Circuit breaker
Line mode overload	>(110%±10)% fault after alarm 1min >(120%±10)% fault immediately
Battery mode overload	>(110%±10)% fault after alarm 1min >(120%±10)% fault immediately
Indicators type	
LED & Alarm	Load Capacity, Load & Battery level, AC mode, Battery mode, Fault indicators
Protection	
Outlets type	4 x Schuko Battery Backup 2 x RJ11/45 (IN/OUT) for modem/ phone/LAN surge protection
Full protection	Overload, Over voltage, Short Circuit, Over discharge and Over charge
Environment	
Noise level	Less than 40dB
Humidity	0-90 % (non-condensing)
Temperature	0-40°C



4 x Schuko outlets with protection



Auto-Restart



Simulated sinewave

- Simulated sinewave
- Auto-Restart while AC is recovering
- Auto-Charge
- Automatic Voltage Regulation (AVR)
- Off-Mode Charging
- Cold start function

Battery

Battery Type & Number 2 x GP09122L
(PN: BTVACGUEBTC2LBTO1B)

Typical Recharge Time 6 hours up to 90% capacity

Running time on battery (minutes)
25% Load - 22 min
50% Load - 8 min
75% Load - 2 min
100% Load - <1 min

Management

Communication port HID USB / LAN

Software <http://www.powermonitor.software/>

Physical


Product dimensions 298 x 148 x 178 mm

Product weight 9.1 kg


Retail pack dimensions 335 x 193 x 246 mm

Retail pack Weight 9.55 kg

Power cord 1.2 m length



Running time on battery



Logistics

Carton Box Size (LxWxH)	612 x 359 x 278 mm
Pieces in the Carton Box	3
Net & Gross weight / CTN	NW: 28.65 kg / GW: 29.41 kg



Certificates

RoHS
2011/65/EU

