

ENERGY EQUIPMENT

PORTABLE GENERATORS



Portable Gasoline Generator 3.5kVA/2.8kW - 230V(50Hz) RE











General Specifications

Engine Model	210
Standby Power (kVA)	3,5
Standby Power (kW)	2,8
Prime Power (kVA)	3,12
Prime Power(kW)	2,5
Rated Current	10,8

- 1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.
- 2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Technical Specifications

Maximum Power (kW / kVA)	2,8 / 3,5
Continous Power (kW / kVA)	2,5 / 3,12
Rated Current	10,8
Number of phases	1 (Single phase)
Voltage (V)	230
Frequency	50
Display	Analog
Engine Type Single	Single Cylinder Air Cooled
Engine Model	210
Engine Power Hp	7
Displacement	208
Starting System	Recoil / Electric
Fuel Type	Gasoline
Fuel Tank Capacity (Lt)	17
Fuel Consumption (Lt /Hour)	1,3
Oil Capacity (Lt)	0,6
Oil Type	15W4O
Noise Level (dBA-7m)	68
Weight (Kg)	50
Dimensions (LxDxH mm)	620x470x530

Polytrade Global SRL reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

www.polytrade.global 1 / 1