

## H1Z2Z2-K 1x240 CL-5 RM 1kV(AC)/1.5kV(DC), Outersheath Color: Black 9011

### Description

Solar cable H1Z2Z2-K is TUV certified, with max. permissible tension DC 1.8 kV, is used in solar energy production applications. It is usually installed outdoor, in the air, on cable trays, ducts or direct burried. With UV resistant outersheath the cable can be posed in direct sunlight, but it is recommended to be protected in order to ensure a service life of 25 years or longer. The cable reation to fire has been tested according to CPR regulation and has received the category Cca-s2,d2,a1. Also, the cable has water resitance for permanent immersion AD8 as per NF C15-100.

### Standards

EN 50618  
IEC 60332-1-2  
IEC 61034-2  
IEC 60228  
EN 50525-1  
EN 50339  
EN50575  
EN 50618

### Construction

**Conductor:** Tinned fine copper strands Class 5  
**Insulation:** Cross-linked Halogen Free compound  
**Sheath:** Cross-linked Halogen Free compound

**Specifications**

Cable Type	Single Core
Cable Overall Diameter	28 mm
Cable Weight	2394 kg/km
Diameter & Weight Tolerance	±5%
Conductor Material	Copper
Number of Conductors	1
Conductor Cross-Section	240 mm <sup>2</sup>
Conductor Weight	1984.6 kg/km
Conductor Class	CL-5
Conductor Type	RM
Insulation Material	XLPE
Outersheath Material	XLPE
AC/DC Rated Voltage (U <sub>o</sub> /U)	1kV(AC)/1.5kV(DC)
Conductor DC Resistance @ 20°C	0.082 Ω/km
Current Carrying Capacity (Air Installation with ambient temperature 60°C)	775 A
Max. Permissible Operating Temperature	90 °C
Working Temperature	-40 >< +90 °C
Short Circuit Temperature	250 °C
Minimum Bending Radius (Installing)	5xD
Minimum Bending Radius (Operating)	5xD
Packing	Wooden Drum, Plywood Drum, Coil, Rolls
Delivery Lengths	To be confirmed by offer
Delivery Length Tolerance	±5%

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.