



Description Interruttore automatico scatolato  
 Code MSX 125  
 No. of poles 3P  
 Rated current 125 A  
 Release Electromechanic

#### ELECTRICAL CHARACTERISTICS

Standard	IEC/EN 60947-2
Use category	A
Rated frequency (Hz)	50 / 60
Rated operating voltage (Ue)	690 Vac - 250 Vdc
Rated impulse withstand voltage (Uimp)	8 kV
Oversvoltage category	IV
Insulation voltage (Ui)	800 V
Thermal regulation	0,63 - 0,8 - 1 x In
Magnetic regulation	6 - 8 - 10 x In
Neutral protection	-
Total power loss	29.52 W
Rated short-circuit current making capacity (Icm)	-
Rated short-time withstand current for 0,3s (Icw)	-
I <sub>dn</sub> regulation	-
DT regulation	-

#### MECHANICAL CHARACTERISTICS

Execution	Fixed - Plug-in
DIN rail mounting	Yes, by means of accessory
Can be equipped with motor operator	Yes
Compatible interlock	Lever - Cable
Terminals supplied	Front FC
Assembly position	Any
Upline/downline power supply	Yes
Electrical life (415Vac)	30.000 cycles
Mechanical life	30.000 cycles
Operating temperature	-5°C +65°C
Stocking temperature	-20° +65°
Weight (kg)	1.1
Width	90 mm
Height	155 mm
Depth	68 mm


#### SERVICE BREAKING CAPACITY (ICU)

220/240Vac	50 kA
400/415Vac	36 kA
440Vac	25 kA
525Vac	22 kA
690Vac	6 kA
250Vdc	25 kA

#### RATED BREAKING CAPACITY (ICS)

220/240Vac	50 kA
400/415Vac	36 / 30 kA
440Vac	25 kA
525Vac	22 kA
690Vac	6 kA
250Vdc	19 kA

### DIMENSIONAL





Product Data Sheet

GWD9126

MSX

STANDARDS/APPROVALS

