

Power Base 1000

PN: ESPS-10HBAKU-CT012
EAN: 6422956013158

Specifications

Capacity	1021 Wh
Input	
USB Type C	Power Delivery (100W Max)
DC 7909	AC power adapter (240W Max) Solar panel with MPPT 12V-32V (240W Max) Car port adapter DC 12V (120W Max)
Output	
USB-A x2	5Vdc/3A, 9Vdc/2A, 12Vdc/1.5A (18W Max)
USB Type C	Power Delivery (PD) 5Vdc/3A, 9Vdc/3A, 12Vdc/3A, 15Vdc/3A, 20Vdc/5A (100W Max)
DC 5525	230V (120W Max) for Router, CPAP breathing machine
Car Port	12V (120W Max)
AC Schuko x2	230V (600W Max)
AC(Sine Wave)	230V/50-60Hz Stable 1000W & Max Output 1200W
Transfer Time	Typical 4 ms
Waveform (Batt. Mode)	Simulated Sine Wave
Cell Chemistry	Li-ionNCM
Single Cell Capacity	46Ah@3.7V/pcs
Lifecycle	1000+ Cycles to 80% Capacity
Indicator	App / LED screen
Software	TUYA App
Storage	
Storage Temp	-4°F~140°F (-25°C~60°C)



USB-A/C
Output/Input






Li-ion NCM



Solar recharge

- 4 Way Recharge
- MPPT Charge Controller
- APP / LCD Screen
- 1000+ Cycles to 80% Capacity
- Li-ion NCM

Logistics

	Carton Box Size (LxHxW)	425 x 258 x 345 mm
	Pieces in the Carton Box	1
	Net & Gross weight / CTN	NW: 9.2kg / GW: 12kg

Certificates

RoHS
2011/65/EU

CE

Operating Temp	32°F~104°F(0°C~40°C)
Battery	
Battery Management System	Over Voltage Protection, Over Current Protection, Over Discharge Protection, Short Circuit Protection(OVP, OCP, ODP, SCP)
Solar Charge System	MPPT Charge Controller
Internal resistance	3 Ω
Physical	
Material	ABS+PC
Product dimensions	340 x 178 x 230 mm
Product weight	9.2 kg
Retail Pack Dimensions	425 x 258 x 345 mm
Retail Pack Weight	12 kg



Logistics

	Carton Box Size (LxHxW)	425 x 258 x 345 mm
	Pieces in the Carton Box	1
	Net & Gross weight / CTN	NW: 9.2kg / GW: 12kg

Certificates

