

Portable Gasoline Generator 10kVA/8kW - 230/400V(50Hz) RE



General Specifications

Engine Model	460
Standby Power (kVA)	10
Standby Power (kW)	8
Prime Power (kVA)	9.4
Prime Power(kW)	7.5
Rated Current	13.5

1) Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2) Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Technical Specifications

Maximum Power (kW / kVA)	8 / 10
Continous Power (kW / kVA)	7.5 / 9.4
Rated Current	13.5
Number of phases	3 (three-phase)
Voltage (V)	230 / 400
Frequency	50
Display	Analog
Engine Type Single	Single Cylinder Air Cooled
Engine Model	460
Engine Power Hp	18
Displacement	460
Starting System	Recoil / Electric
Fuel Type	Gasoline
Fuel Tank Capacity (Lt)	28
Fuel Consumption (Lt /Hour)	3
Oil Capacity (Lt)	1.3
Oil Type	15W40
Noise Level (dBA-7m)	75
Weight (Kg)	87
Dimensions (LxDxH mm)	720x530x610

Polytrade Global SRL reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.